

HLF P16

TRAILER MOUNTED ARTICULATED BOOM LIFT



- Hydraulic outriggers, easy to set up
- Compact trailer mounted boom lift
- Proportional controls, smooth and easy to operate
- Simple to maintain

STANDARD FEATURES

- 230V ac + petrol powered
- Hydraulic outriggers
- CE approved

WWW.HLFAS.COM

Technical data P16

Max.working height	15,80 m
Max.platform height	13,80 m
Loading capacity	200 Kg
Lateral outreach	7.00 m
Jib rotation	100°
Turntable rotation	359°
Size of basket	0.90 x 0.80 x 1.10 m
Overall stowed length	6.50 m
Overall stowed width	1.53 m
Overall stowed height	2.10 m
Length outrigger footprint standard	3.95 m
Width outrigger footprint standard	3.15 m
Total weight	2.000 Kg
Traveling speed	80 Km/h

Technical specifications P16

Multiple job site application,indoors and outdoors
Hydrastatic self-leveling platform
Basket and turret operation panel
Hydraulically arms and outrigger interlocks
359°non-continuous turntable rotation
Made of high strength steel
Complete documentation: Operator manual, electronic and hydraulic diagrams
Safety and reliability: Complies with or exceeds all by ISO manufacturing standards, e.g. CE-approval
Manufactured according to: EN 280