

HLF P18

TRAILER MOUNTED ARTICULATED BOOM LIFT



- Hydraulic outriggers, easy to set up
- Compact trailer mounted boom lift
- Proportional controls, smooth and easy to operate
- Simple to maintain

STANDARD FEATURES

- 230V ac + petrol powered
- Hydraulic outriggers
- CE approved

WWW.HLFAS.COM

Technical data P18

Max.working height	18.00 m
Max.platform height	16.00 m
Loading capacity	200 Kg
Lateral outreach	7.00 m
Jib rotation	120°
Turntable rotation	359°
Size of basket	0.90 x 0.80 x 1.10 m
Overall stowed length	5.95 m
Overall stowed width	1.62 m
Overall stowed height	2.40 m
Total weight	1.950 Kg
Traveling speed	80 Km/h

Technical specifications P18

Covers on outrigger cylinders
Multiple job site application,indoors and outdoors
Hydrostatic self-leveling platform
Basket and turret operation panel
Hydraulically arms and outrigger interlocks
359°non-continuous turntable rotation
Made of high strength steel
Complete documentation: Operator manual, electronic and hydraulic diagrams
Safety and reliability: Complies with or exceeds all by ISO manufacturing standards, e.g. CE-approval
Manufactured according to: EN 280:2001+A2:2009